

CROWN-15



Key cutting machine for tubular keys with frontal cuts.
Standard version supplied with synchronised selfcentering clamp (T15) for tubular keys.

The synchronisation device automatically rotates the key blank proportionately as the original key is rotated.
Rotation may be free through 360° or set to stop in 6 or 8 predetermined positions, by operating a selector.





11 additional clamps are available on request for special requirements.















Machine built to CE standards.



Tubular keys

Ø UNIVERSAL mm6...mm12,5 - Internal cuts

OPTIONAL					
 <p style="text-align: right;">Interchangeable device</p>					
 For PROGRES-FONTAINE CORNI (5) T2 D700189ZB	 For PROGRES-FONTAINE CORNI (7) T3 D700190ZB	 For VIGIE-PICARD (6) T4 D700191ZB	 For LAPERCHE (6) T5 D700192ZB	 For JPM (5) T6 D700193ZB	 For DAD-DECAYEUX (5) T7 D700194ZB
 For POLLUX (5) T8 D700195ZB	 For POLLUX (7) T9 D700196ZB	 For CAVITH T13 D700199ZB	 For VIGIE-PICARD (8) T14 D704534ZB	 For GB2 T17 D709355ZB	

CROWN-15



TECHNICAL DATA

Motor:	Single-phase motor
Cutting tool:	Ø 5,95mm
Dimensions:	width 230 mm - depth 450 mm - height 180 mm
Weight:	17Kg



AVAILABLE VERSIONS

<i>CROWN-15 230V/50Hz</i>	Code D806575ZB
---------------------------	----------------